

## PEB-10G/57811-1S

---

**Controller**BCM 57811S

**Data Transfer Rate**10 Gbps Ethernet

**Connection Ports**Single Port, SFP+

**Host Interface**PCIe 2.0 x8

**Module Type**SFP+ SR/LR Optical Module  
AOC (Active Optical Cable)  
DAC (Direct Attached Copper)

**Jumbo Frame**Yes (9.5 KBytes)

**RDMA**No

**Boot Support**Pre-eXecution Environment (PXE)  
iSCSI boot  
FCoE boot

**Form Factor**Low-profile Card

**Dimensions**4.72 x 1.77 Inch

**Package Content**

- 1 x Card with Full-height Bracket
- 1 x Low-profile Bracket with Screws
- 1 x Small Bracket(for Node) with Screws
- 1 x Support DVD (per carton)

**Note\***All specifications are subject to change without notice.

- Products certified by the Federal Communications Commission and Industry Canada will be distributed available products.
- All specifications are subject to change without notice. Please check with your supplier for exact offers.
- Specifications and features vary by model, and all images are illustrative. Please refer specification page
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.
- The information contained is general testing result for reference. Please consult local sales representative

Want More?

---

Who We Are

---

Need Help?

---

Community

---

Global / English

[Terms of Use Notice](#) | [Privacy Policy](#) | ©ASUSTeK Computer Inc. All rights reserved.