

## PEB-10G/57840-2S

---

**Controller**BCM 57840S

**Speed**10 Gigabit/s Ethernet

**I/O Ports**SFP+ ; Dual Port

**Connector**LC Fiber Optic

**Module Type**Supports SFP+ SR Optical Module, SFP+ LR Optical Module, Direct Attached Copper

**Interface**PCI-E Gen3 x8

**Form Factor**4.72"x 1.77"  
(Lower Than Standard Low-profile)

**Cable**Support Cable Type :  
SMF up to 10km (LR)  
MMF 62.5/50um up to 300m (SR)  
Passive Twin-AX up to 5m (SFP+ Direct Attach)

**Features**PXE Boot  
iSCSI Boot

**Package Content**1 x Full-height Bracket (Default)  
1 x Low-profile Bracket with Screws

[Need Help?](#)

1 x Small Bracket(for Node) with Screws  
1 x Support DVD (per carton)

**Note\*** All specifications are subject to change without prior notice.

- All specifications are subject to change without notice. Please check with your supplier for exact offers. Products ma
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.

Want More?

---

Who We Are

---

Need Help?

---

Community

---

United States / English

[Terms of Use Notice](#) | [Privacy Policy](#) | ©ASUSTeK Computer Inc. All rights reserved.



Need Help?