

## PIKE II 3008-8i

---

**Chipset**LSI SAS 3008

**Interface**PCI-E Gen 3

**Ports**8 Ports \*1

**RAID levels**RAID 0/RAID 1/RAID 10/RAID 1E

**Devices Supported****SATA :**

SATA 3Gb/s, SATA 6Gb/s

**SAS :**

SAS 3Gb/s, SAS 6Gb/s, SAS 12Gb/s

**Data Rate**SAS 12Gb/s

**Form Factor**5.81 " x 2.71 " Inch

**Package Content**1 x Full-height Bracket (Default)

1 x Low-profile Bracket

1 x HDD LED Cable

1 x Support DVD (per carton)

**Note**\*1 8 SAS 12Gb/s Ports(2 Mini-SAS HD SFF-8643)

\*Support ASUS server and workstation motherboard/system :

(1) Z10PE-D16 Series, Z10PR-D16, Z10PH-D16, Z10PA-D8 Series, Z10PA-U8

[Need Help?](#)

Series, Z10PE-D8 WS, Z10PE-D16 WS, X99-E WS  
ESC8000 G3, ESC4000 G3S Series, ESC4000 G3 Series, RS700-E8 Series,  
RS720-E8-RS24-E, RS500-E8 Series, RS520-E8 Series, RS720Q-E8-RS12,  
TS500-E8-PS4, TS700-E8 Series

(2) Z9PE-D16-10G/DUAL Series, Z9PE-D16 Series, Z9PH-D16 Series, Z9PR-D16, Z9PR-D12, Z9PA-D8 Series, Z9PA-U8 Series, Z9NR-D12, Z9NA-D6 Series, Z9NH-D12, Z9PE-D8 WS  
RS700-E7 Series, RS720-E7/R24-EG, RS720-E7/R12 Series, TS700-E7/R8,  
RS720Q-E7/R12 Series, TS700-X7/PS4

\*\* Ensure to update BIOS to the latest version before using PIKE II 3008 Series card.

(3) P9D-E/4L, P9D-C/4L, P9D-MH Series, P9D-M, P9D-MV, P9D-V, P9D-X, P9D-I, P9D-IV, P9A-I Series

\*\* Ensure to update BIOS to the latest version before using PIKE II 3008 Series card.

- All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.

Want More?

---

Who We Are

---

Need Help?

---

Community

---

United States / English

[Terms of Use Notice](#) | [Privacy Policy](#) | ©ASUSTeK Computer Inc. All rights reserved.



Need Help?