Products What's Hot Commercial

## Specifications

Processor / System Bus2 x Socket R3 (LGA 2011-3) Intel® Xeon® processor E5-2600 v3 product family(145W)\* Intel® Xeon® processor E5-2600 v4 product family (145W) \* QPI 6.4 / 8.0 / 3.6 GT/s \*Refer to support page for more information

## Generation<sup>E8</sup>

Core LogicIntel® C612 PCH

Memory/Memory Type:
1600/1866/2400/2133 KIDIMM DDR4
DDR4 15000/1866/2400/2133 RDIMM
Total Slots: 16 (4-channel per CPU, 8 DIMM per CPU)
Capacity: Naimamum up to 1024GB LRDIMM
Memory Size:
4GB, 32GB, 16GB, 8GB RDIMM
64GB, 32GB, 16GB, 8GB RDIMM

ACUS CALIMINIA

\*\*Actual memory frequency differs from Intel CPU types and memory module.

\*\*Please check Intel official site for more detail about the memory types supported by each CPU.

\*\*Refer to support page for more information

## Expansion Slots<sup>2</sup> + 1

\* Support for MCB-10G-2S (Dual Port 10 Gigabit/s Ethernet card) (optional)

StorageSATA Controller:
Intel® Rapid Storage Technology Enterprise(RSTe) (For Windows Only)
(Support Software RAID 1, 10, 5, 0)
1 x M2 connector
9 x SATA3 6Gbl/s ports (8 by 2 mini-SAS Connector)
Intel® C612
SAS Controller:
ASUS PIKE II 3108 8-port SAS HW RAID card(Optional)
126 SAS Support

12G SAS Support ASUS PIKE II 3008 8-port SAS HBA card(Optional)

HDD Bays4 x Hot-swap 3.5" Storage Bays 1 x M.2 (NGFF 2242)

Auxiliary Storage FDD/CD/DVD1 x Slim-type Optical Drive Bay Options: No Device / DVD-RW

Networking2 x Intel® I210AT + 1 x Mgmt LAN

GraphicAspeed AST2400 with 32MB VRAM

Front I/O Ports2 x USB 2.0 ports

Rear I/O Ports2 x RJ-45 ports 1 x RJ-45 Mgmt LAN port 2 x USB 3.0 ports 1 x VGA port 1 x PS/2 KB/MS port

Switch/LEDFront Switch/LED:

1 x Power switch/LED

1 x Location switch/LED

1 x Location switch/LED

1 x Reset switch

1 x HDD Access LED

1 x Message LED

LAM 1-4 LED

\* LAN 3-4 for Mezzazine card use

Rear Switch/LED: 1 x Q-Code/Port 80 LED 1 x Power switch/LED 1 x Location LED 1 x Message LED

OS SupportUbuntu Windows® Server 2016 Windows® Server 2012 R2 Windows® Server 2008 R2

SuSE® Linux Enterprise Server Windows® Server 2012 Citrix XenServer

\*Subject to change without any notice VMware CentOS RedHat® Enterprise Linux

Management SolutionASWM Enterprise On-Board ASMB8-iKVM for KVM-over-IP

Regulatory ComplianceCE, BSMI, C-Tick, FCC(Class A)

Dimensions615mm x 444mm x 44mm 24.21" x 17.48" x 1.73"

Form Factor10

WeightNet Weight: 10.93 Kg Gross Weight: 17.18 Kg

Power Supply1+1 Redundant 770W 80 PLUS Platinum Power Supply

Rating: 100-127Vac/200-240Vac,10A/5A ,50-60Hz, Class I

 $\label{eq:continuous} Environment Operation temperature: 10 ^{\circ}C \sim 35 ^{\circ}C \\ Non operation temperature: -40 ^{\circ}C \sim 70 ^{\circ}C \\ Non operation humidity: 20 ^{\infty} \sim 90 ^{\infty} ( Non condensing) \\$ 

29/07/2018 19:12 1 de 2

- Products certified by the Federal Communications Commission and Industry Canada will be distributed in the United States and Canada. Please visit the ASUS USA and ASUS Canada websites for information about locally available products.
  All specifications are subject to change without notice. Fresher berde with your supplier for exact offers. Products may not be available in all markets.
  Specifications and features vary by model, and all images are illustrative. Please refer specification pages for full details.
  PCB color and bundled software versions are subject to change without notice.
  Brand and product names mentioned are trademarks of their respective companies.

The information contained is general testing result for reference. Please consult local sales representative for more information on specific supported CPU list on each system.

Want More? Who We Are Need Help? Community TUF Gaming About ASUS Check Repair Status **y** (f) (h) (p) News Awards Asus Design Center Product Registration Investor Relations ROG Email Us Automotive Solutions Press Room Security Advisory

ASUS HealthCare

Terms of Use Notice | Privacy Policy | ©ASUSTEK Computer Inc. All rights reserved. Global / English

Windows 10 S Compatible Device

2 de 2 29/07/2018 19:12