

[Products](#)[What's New](#)[Commercial](#)[Support](#)[Store](#)[LOGIN](#)

Specifications

Processor / System Bus2 x Socket R3 (LGA 2011-3)
Intel® Xeon® processor E5-2600 v4 product family (160W) *
Intel® Xeon® processor E5-2600 v3 product family(160W)*
QPI 6.4 / 8.0 / 9.6 GT/s
*Refer to support page for more information

GenerationE8

Core LogicIntel® C612 PCH

Memory**Total Slots** : 16 (4-channel per CPU, 8 DIMM per CPU)
Capacity : Maximum up to 1024GB LRDIMM

Memory Type :
DDR4 2400 /1866*/2133 /1600 RDIMM
DDR4 2400 /1866*/2133 /1600 LRDIMM

Memory Size :
32GB, 16GB, 8GB, 4GB RDIMM
64GB, 32GB LRDIMM

* Refer to support page for more information
* Actual memory frequency differs from Intel CPU types and memory module.
Please check Intel official site for more detail about the memory types supported by each CPU.

Expansion SlotsTotal slot:6

4 x PCI-E x16 (Gen3 x16 link), FH, FL
1 x PCI-E x16 (Gen3 x8 link), FH, FL
1 x PCI-E x16 (Gen3 x8 link), FH, HL

Storage**SATA Controller** :

Intel® C612
10 x SATA3 6Gb/s ports
or
9 x SATA3 6Gb/s ports + 1 x M.2 connector
Intel® Rapid Storage Technology Enterprise(RSTe) (For Windows Only)
(Support Software RAID 0, 1, 5, 10)

SAS Controller :
ASUS PIKE II 3008 8-port SAS HBA card(Optional)
ASUS PIKE II 3108 8-port SAS HW RAID card(Optional)
12G SAS Support

HDD Bays4 x 3.5" Hot-swap Storage Bays
1 x M.2 (NGFF 22110/2280/2260)

Auxiliary Storage FDD/CD/DVD3 x 5.25" media bays
(Options: No Device / DVD-RW)

Networking2 x Intel® I210AT + 1 x Mgmt LAN

GraphicAspeed AST2400 with 32MB VRAM

Multi-GPU SupportSupport ATI® CrossFire™ technology, up to
Quad CrossFireX
Supports NVIDIA® 2-Way Geforce SLI™ technology

Front I/O Ports1 x Headphone jack
1 x Microphone jack
2 x USB 2.0 ports
2 x USB 3.0 ports

Rear I/O Ports2 x RJ-45 ports
1 x RJ-45 Mgmt LAN port
4 x USB 3.0 ports
4 x USB 2.0 ports
1 x PS/2 KB/MS port
1 x S/PDIF Out (Optical)
1 x Set of Audio ports (6 Ports)
1 x VGA port

Switch/LEDFront Switch/LED:

1 x Power switch
1 x Location LED
1 x Reset switch
1 x HDD Access LED
1 x Message LED
1 x Power LED
LAN 1-2 LED

Rear Switch/LED:

1 x Q-code Logger button w/ LED
1 x BIOS flashback button w/ LED

OS SupportWindows® Server 2016

Windows® Server 2012 R2
Windows® Server 2012
Windows® Server 2008 R2
RedHat® Enterprise Linux
SuSE® Linux Enterprise Server
CentOS
Ubuntu
VMware
Citrix XenServer

*Subject to change without any notice

Management SolutionASWM Enterprise
On-Board ASMB8-iKVM for KVM-over-Internet

Regulatory ComplianceBSMI, CE, C-Tick, FCC(Class B)

[Need Help?](#)

Dimensions	445mm x 545mm 17.91" x 8.54" x 21.45"
Form Factor	SU/Tower
Weight	Net Weight: 17.20 Kg Gross Weight: 24.00 Kg
Power Supply	Single 1200W 80PLUS Platinum Power Supply 1000W: 100-114.9Vac, 12-8A, 50-60Hz, Class I 1200W: 114.9-240Vac, 12-8A, 50-60Hz, Class I
Environment	Operation temperature: 10°C ~ 35°C Non operation temperature: -40°C ~ 70°C Non operation humidity: 20% ~ 90% (Non condensing)

- All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.

Want More?

TUF Gaming
ASUS ROG
Powered By ASUS
Rebate Center
ASUS Advantage
Deal Registration
Become a Reseller
Insider's Edge
Edge Up

Who We Are

Where to buy
About ASUS
Latest News
Awards
Investor Relations
Corporate Social Responsibility
Careers
Press Room

Need Help?

Contact Us
ASUS Store
Commercial Support
Product Registration
Security Advisory

Community



United States / English

[Terms of Use Notice](#) | [Privacy Policy](#) | ©ASUSTeK Computer Inc. All rights reserved.